

## PRODUCT DATA SHEET

### CG CLEAR ERASE TRANSPARENT FILM

#### Features:

- 100 micron transparent PET with erasable coating
- Clear permanent adhesive
- 75micron PET Liner
- Transparent protection film with excellent flatness
- 100,000 times erasable

#### Areas of application:

- Image protection of the advertising material
- School supplies, office stationery, family memos

#### Application requirement:

- Installation
- Make the lamination in a clean dust-free environment without suspended matter
- Begin the cold lamination and other operation after the image is complete dry

#### Storage condition:

- Temperature of 10 ~ 25° C, relative humidity of 50% ± 10%
- Store in the original packing and with the original protection materials
- Preferably no more than 6 layers if stored horizontally
- Do not expose in direct sunlight or heat sources

#### Warranty:

- Shelf life: 1 year, stored in original carton box, preferably use within 6 months
- Prosecution Period: 1 year from the product manufacture date, no-acceptance for overdue product

Test Items	units	Average value
Thickness - PET film	Micron	100 ± 10
Weight - Adhesive	g/m <sup>2</sup>	25 ± 5
Weight - Liner	g/m <sup>2</sup>	105 ± 20
Initial adhesion	N/25mm	≥ 5
180° peel off (30min)	N/25mm	≥ 12
Dimensional stability (along side)	mm	No shrinkage
Dimensional stability (across side)	mm	No shrinkage
Construction Temperature	°C	20 ± 10
Applicable Temperature	°C	-20 ~ +70
Temperature resistance	Adhered to aluminum. -20C to +65C , no variation	
Seawater resistance	Adhered to aluminum, after 48h/23C no variation	

All information stated within this Product Data Sheet is intended for reference purposes only. The information does not suggest or constitute a verbal or written warranty. The end user shall be responsible for the testing and suitability of their application prior to final use.