

PRODUCT DATA SHEET

CG MATT SYNTHETIC FILM

CG Synthetic Film is a 240 micron matt finish PP film ideal for tear resistant and waterproof posters. CG Synthetic film is compatible with Solvent, Latex and UV Curable Inks.

PRODUCT FEATURES

- Indoor / Outdoor advertising
- Compatible with latex, solvent, and UV ink
- Excellent colour reproduction
- Fast drying

TECHNICAL DATA

Testing condition: Indoor temperature $23\pm 2^{\circ}$, Relative humidity $50\pm 5\%$.

Test Term	Unit	Test Method	Average
Weight-finished product	g/m^2	GB/T4669	170 ± 20
Tensile strength at MD	N/5cm	GB/T1040	≥ 200
Tensile strength at CD	N/5cm	GB/T1040	≥ 300
Applicable Temperature	C		$-20\sim +70$

INSTALLATION

We suggest you allow 24-48 hours for the print to dry prior to lamination. Always clean application free of dust, dirt, debris and other contaminants. We recommend cleaning the installation surface with isopropyl alcohol prior to application.

All information stated within this Product Data Sheet is intended for reference purposes only. The information does not suggest or constitute a verbal or written warranty. The end user shall be responsible for the testing and suitability of their application prior to final use.