

PRODUCT DATA SHEET

DIGISAV

Starflex Digisav is a 100 Micron promotional grade white digital vinyl with a grey bubble free removable adhesive. It is the ideal solution for internal or short term outdoor graphics. Its bubble free adhesive allows for easy installation when dry applied. Compatible with Solvent, Eco Solvent, Uv and Latex printing technologies.

APPLICATIONS

- General Stickers & Decals
- Exhibition Boards
- Realestate Signage
- Point of Sale
- Window Graphics
- Shopping Centre Hoardings

TEST ITEM	TEST METHOD	SPECIFICATION
PVC Film Thickness	100µm± 10µm	ISO 4591 : 1992
Adhesive type		Solvent polyacrylate Removable, Grey
Release paper		Embossed 140 gsm Double side PE-Coated
Dimensional stability	FINAT TM14	Adhered to steel, no shrinkage in cross direction
Temperature resistance		Adhered to aluminum. -20 to +65C
Seawater resistance	DIN 50021	Adhered to glass, after 48H/20C, no variation
Adhesive power	FINAT TM1	After 24h, stainless steel 6-10N/25mm
Tensile strength	ASTM D882-02;200MM/MIN	min.24MPa min.23MPa
Application temperature		Min. +10C
Weathering		

INSTALLATION

Before applying an overlaminate, we suggest you allow 24-48 hours for the print to dry. Always clean application free of dust, dirt, debris and other contaminants. We recommend cleaning the installation surface with isopropyl alcohol prior to application.

All information stated within this Product Data Sheet is intended for reference purposes only. The information does not suggest or constitute a verbal or written warranty. The end user shall be responsible for the testing and suitability of their application prior to final use.