

PRODUCT DATA SHEET

Admiral

H966 DOUBLE COATED TAPE

CHARACTERISTIC	VALUE
ADHESIVE	ACRYLIC (SOLVENT BASED)
TACK	J.DOW NO. 16
LINER	3MIL LIGHT PINK MOPP FILM
CARRIER	1/2MIL (12μ) CLEAR PET FILM
PEEL ADHESION	PSTC-3 1.8KGS/25MM
SHEAR STRENGTH	PSTC-7 OVER 24 HOURS WITH 2KG LOADING ON 25MM X 25MM
THICKNESS	0.20 ± 0.01MM
HEAT RESISTANCE	OVER 24 HOURS WITH 0.5KG LOADING ON 25MM X 25MM AT 80°C
TENSILE STRENGTH	MD 20KG/MM2↑ TD 20KG/MM2↑
ELONGATION	MD 110 %↑ TD 100 %↑
SERVICE TEMPERATURE	-20 TO 180°C (SHORT TIME) <i>will go to 120°C for up to a week</i>

PRODUCT FEATURES AND APPLICATIONS

MOUNTING ON ABS PLASTIC PLATES IN INDUSTRIAL APPLICATIONS
 SELF ADHERING JOINING OF RUBBER AND EPDM MATERIALS
 BONDING TO DECORATIVE TRIM SUCH AS PVC PROFILES, STAINLESS STEEL, PLASTICS

All information stated within this Product Data Sheet is intended for reference purposes only. The information does not suggest or constitute a verbal or written warranty. The end user shall be responsible for the testing and suitability of their application prior to final use.