

TECHNICAL DATA SHEET

SC510 Spread Coated Matt Frontlit Banner Grey Back

Weight: 510gsm

Denier: 1000 x 1000

Yarn: 12 x 12

Property	Test Method	Value	Unit
Tensile Strength (warp/weft)	ISO 13934-1 : 2013 C.R.E.STRIP METHOD	2400 2300	N/50mm
Tearing Strength (warp/weft)	ISO 13937-2 : 2000 C.R.E.SINGLE TOUNGE METHOD	169 126	N
Elongation (warp/weft)	ISO 13934-1 : 1999 C.R.E.STRIP METHOD	21.5 25.5	%
Adhesion Strength (warp/weft)	ISO 2411 : 2000	81 82	N/5cm
Resistance to Flexing	DIN 53351 : 1973 TEST CONDITION : 20C, 400 CYCLES	NO CREAKING	

APPLICATIONS

High quality, long life rope, eyelet & sail track banners
Internal & external close view banners
Display banners with no edge curl


COMPATIBLE INK TECHNOLOGY

Solvent
Latex
UV Curable

AVAILABLE WIDTHS in 50m lengths

1370mm, 1600mm, 2200mm & 2500mm

FREE ROLL SLITTING SERVICE AVAILABLE



Unit 22 / 1029 Manly Rd, Tingalpa QLD 4173

P (07) 3890 5414 F (07) 3890 5701

ABN 49 163 849 232 ACN 163 849 232

creativegraphicsupplies.com.au