



## PRODUCT DATA SHEET

### PET BACK LIT FILM 205MICRON - FSB205M

205 Micron PET Matt backlit film compatible with Solvent, Eco Solvent, Uv and Latex printing technologies.

#### Product Features

- 205 micron Matt Front Print Polyester Backlit Film
- Compatible with Solvent, Eco Solvent and Latex Ink
- Excellent Colour Definition when Illuminated or Non Illuminated
- Special Top Coating allows for Fast Drying
- Ideal for Indoor / Outdoor Lightbox Signage and Menu Displays

#### TECHNICAL DATA

Technical Data		
	Result	Test Method
Caliper	205 micron	ASTM D645
L.A.B	85/1/-7	ANSI T (D50/2deg/Abs/No)
Yellowness	30	ASTM D1925
Glossiness	5 - 8	ASTM D2457
Specification		
Caliper	205 micron	
Weight	275 gsm	
Base Materials	PET	
Surface	Matt	

#### INSTALLATION

Before applying an overlaminate, we suggest you allow 24-48 hours for the print to dry. Always clean application free of dust, dirt, debris and other contaminants. We recommend cleaning the installation surface with isopropyl alcohol prior to application.

All information stated within this Product Data Sheet is intended for reference purposes only. The information does not suggest or constitute a verbal or written warranty. The end user shall be responsible for the testing and suitability of their application prior to final use.

